


sauermann[®]

KIMO[®]
INSTRUMENTS



MEASURING INSTRUMENTS

Export General Catalogue





For more than 45 years, the Sauermann Group has designed, manufactured and sold products and services dedicated to industrial and HVACR markets. The Group specifically focuses on the detection, measurement and control of indoor air quality (IAQ).

**LOW NOISE LEVEL
HIGH RELIABILITY
HIGH PERFORMANCE**

Condensate management solution: Safe and efficient condensate management in air quality systems can be challenging. The design of Sauermann pumps is carefully engineered. Patented technologies ensure that our pumps run quietly and with unmatched reliability.

**HIGH PRECISION
OUTSTANDING RELIABILITY
NUMEROUS APPLICATIONS**

Measuring instruments: Sauermann is specialized in the measurement of many indoor air parameters, designed to monitor buildings' aeraulic systems (air conditioning and heating), cold chain protection and thermal machines' combustion efficiency. Thanks to its extensive test laboratories and in-house research and development, Sauermann's measuring instruments ensure reliability and accuracy for all HVAC operators.



North America

●● Sauermann N.A. Corp.,
New York, Langhorne, USA

**EMEA – Europe,
Middle East & Africa**

● Si Invest SA,
Brussels, BELGIUM

●● Sauermann Industrie S.A.S,
Chevry-Cossigny,
Montpon, FRANCE

● Sauermann GmbH,
Leingarten, GERMANY

● Sauermann UK Ltd.,
Blackpool, UNITED KINGDOM

● Sauermann Iberica,
Barcelona, SPAIN

● Sauermann Italia S.r.l,
Bologna, ITALY

Asia Pacific

●● Sauermann China,
Shanghai (Jiading & Pudong),
CHINA

● Sauermann Australasia,
Sydney, AUSTRALIE

Content

Combustion gas
analysers

04



HVACR
PORTABLE

10



Data loggers

18



Sensor
transmitters

20



Combustion gas analysers 04

- A new degree of efficiency 04
- Features 05
- Si-CA 030 / 130 / 230 06
- Mobile app 09

HVACR Potable 10

- Classes 50 / 110 / 210 / 310 . . . 10
- Multi-function 13
- Thermometers 14
- Infrared 15
- Indoor air quality monitors 16
- Airflow meter 17

Data loggers 18

- Mini / USB / Multi-function 18
- Connected 19

Sensor transmitters 20

- Monostats 21
- Class 110 / 210 R 21
- Multi-function 22

Data acquisition system 24

- Calibration benches 24

Temperature probes 25

- CRYO 25
- Wire probes 25
- ABS head 25
- Connection 25

Manometers 25

- Inclined 25
- Vertical 25
- Differential pressure switch 25
- Accessories 25

Our expertise 26

- Manufacturing / Laboratories 26
- R&D 26

Combustion gas analyzers

A new degree of efficiency



Our combustion gas analyzers are ideal for maintaining combustion equipment, covering the full range of operations in residential, commercial and industrial applications.

Sauermann offers a range of compact and intuitive analyzers to enhance your performance.

Sauermann's combustion gas analyzers feature the latest digital and metrology technologies, making measurements more reliable and cutting the amount of time heating engineers need to spend on-site. A user experience like no other!

Applications

- Boilers
- Burners
- Water heaters
- Gas and diesel engines
- Furnaces
- Industrial kilns
- Industrial heating systems
- Incinerators



Features

Add a digital edge to your combustion analysis



Auto pump cut-off for high CO levels (adjustable)



Predictive maintenance with estimated sensor life & calibration reminders



Draft & differential pressure measurements



Mobile phone app for real-time remote display & control



Calculations for Combustion Efficiency, Excess Air, & CO₂%



Data management with automatic logging & report creation



Si-CA 030



Si-CA 130



Si-CA 230

LCD display size	2.8 inches	4.3 inches	4.3 inches
Display resolution	320 x 240 pixels	480 x 272 pixels	480 x 272 pixels
Touch-screen display	No (5 buttons)	Yes (+ on/off button)	Yes (+ on/off button)
Dimensions (H x W x D)	9,9 x 19,4 x 4,9 cm 7.5 x 3.5 x 1.6"	9,9 x 19,4 x 4,9 cm 7.5 x 3.5 x 1.6"	11,2 x 28 x 5,5 cm 11 x 4.3 x 2"
Weight	350 g - 12 oz	350 g - 12 oz	825 g - 30 oz
No. of cells	Up to 3 (O ₂ , CO, NO)	Up to 3 (O ₂ , CO, NO, Low NO)	Up to 6 (O ₂ , CO, NO, Low NO, NO ₂ , Low NO ₂ , SO ₂ , Low SO ₂ , CxHy, H ₂ S)
Max. CO measurement	8,000 ppm	8,000 ppm	50,000 ppm (with dilution)
CO dilution	-	-	✓
Field replaceable pre-calibrated sensors	-	✓	✓
Flue gas velocity with Pitot tube	-	✓	✓
Measurement storage	Smartphone	Internal: 2,000 data points + Smartphone and PC	Internal: 2,000 data points + Smartphone and PC
PC software (wireless & USB)	-	✓	✓
Smartphone app (wireless)	✓	✓	✓
Combustion Applications	Residential, Commercial	Residential, Commercial	Commercial, Industrial



To see our extensive range of other measurement instruments for heating applications, go to www.sauer mann group.com

Si-CA 030

All the essentials for combustion gas analysis

The Si-CA 030 offers everything heating engineers need to inspect and maintain residential and commercial boilers, with wireless connection to our smartphone app and automatic generation of servicing reports and certificates.



Up to three gas sensors:
O₂, CO and NO (for NOx)



Auto pump cut-off
for high CO levels

- NOx capable with NO sensor
- Quick and easy pump On/Off control
- CO safety monitoring in ambient air


LIGHTWEIGHT
350 g


FREE APP



NATURAL GAS	
O2	4.51 %
CO	80 ppm
Eff. (η)	91.4 %
CO2	12.5 %
T flue	170.3 °C
NO	78 ppm
NOx	82 ppm
Draft	1.094 mbar



Common features Si-CA 030 / Si-CA 130

- Predictive maintenance with estimated sensor life & calibration reminders
- Draft & differential pressure measurements
- Calculated CO₂ % value
- CO safety monitoring in ambient air



**CO measurement up to
8,000 ppm**



Color display

Si-CA 130

Comprehensive, versatile analyzer with touch-screen display

The Si-CA 130 features a touch-screen display and comes with PC-based management software (in addition to the smartphone app) for more in-depth combustion gas analysis. The three field-replaceable cells and sensors offer expanded measurement capability.



Up to three gas sensors O₂, CO, and NO or Low NO (for NO_x)



Field replaceable precalibrated sensors

- Auto pump cut-off for high CO levels (user-adjustable)
- NO_x capable with NO sensor (optional)
- One Touch Pump On/Off with Purge
- PC software with wireless and USB connectivity
- Graphical data display
- Customisable gas analysis screen

- Combustion efficiency and excess air calculations
- Protective rubber casing
- Maintenance agreements and extended warranties available
- Emissions values adjusted for reference O₂




Data management with automatic logging & report creation through app/PC software




Lightweight, only 350 g (12 oz)

19.4 cm - 7.5"



Si-CA 230

State-of-the-art, industrial emissions analyzer



With up to six gas sensors and expanded measurement capabilities, the Si-CA 230 is well suited for boilers, burners, engines, and other industrial combustion applications. And with support for more gases and a high CO tolerance threshold, its versatility makes it the ideal choice across commercial and industrial applications.



Up to Six Gas Sensors.
Can O₂, CO, NO, Low NO, NO₂, Low NO₂, SO₂, Low SO₂, H₂S, and CxHy



CO Dilution auto-range
with measurements to
50,000 ppm



Total NOx & Low NOx
Capable



Field Replaceable
Pre-Calibrated Sensors



Features: Si-CA 230

- Ergonomic, light weight, & durable design
- Data management with automatic logging & report creation
- Predictive maintenance with estimated sensor life & calibration reminders
- One touch pump On/Off with purge
- PC software with wireless and USB connectivity
- Auto pump cut-off for high CO levels
- Graphical data display
- Customisable gas analysis screen
- Stack gas velocity with Pitot tube
- Draft and differential pressure measurements
- Emissions values adjusted for reference O₂
- CO safety monitoring in ambient air
- Protective rubber holster
- Maintenance contracts and extended warranties available

Mobile app

Sauermann Combustion



The Sauermann Combustion app lets you control your Si-CA analyzer remotely, view measurement results in real time, and customise them before exporting in the format of your choice.

- Free apps for iOS & Android mobile devices
- PC software with USB & wireless connectivity
- Fast, easy wireless connection
- Remote live view of combustion analysis data as list or graph
- Remote control to change settings
- Data saving, including automatic logging
- Report creation in PDF, CSV (for Excel) and XML formats
- Databases for customers, operators, & equipment

Download Sauermann Combustion app



Warranty

All devices come with a two-year warranty against manufacturing defects (subject to assessment by our after-sales department).

To find out more about our extended warranties and maintenance plans, please visit our website, or contact our Customer Service Department.



Additional measurements

Gas detection

FG 110

- Detection of gas such as methane (CH₄), LPG (isopropanol and isobutane) and other combustible gases (hydrocarbons)
- Flexible hose



Industrial
Si-CA 8500



O₂, CO, CO₂, NO, NO₂, SO₂, C_xH_y (HC), H₂S, VOC



US EPA CTM-30 and CTM-034 compliant



PID VOC sensor option

Gas network

MP 130

Gas tightness special manometer for gas network

- 0 to ±500 mbar



- Up to 9 gas sensors
- Low NO, NO₂ and SO₂
- Stack gas velocity
- Built-in thermoelectric chiller

- Automatic condensate drain
- High accuracy NDIR sensors
- Upgraded memory (2,000 tests)

HVACR Portable

Instruments

Temperature / Humidity / Pressure / Air velocity / Airflow
Air quality / Gas detection / Light / Tachometry



Class 50, 110, 210 & 310

The range of portable devices is ideal for technicians responsible for maintaining heating, ventilation, and cooling installations.

- Wireless and Smart+ probes
- Graphical wide screen
- Data recording
- Ergonomic design



Graphical display



Magnetic protective cover



IP54 housing




Interchangeable probes & modules

Datalogger

Configure / Measure / Data processing

- Configuration of instruments
- Instruments management
- Reports creation
- Customized channels
- Insert commands
- Insert legends and statistics
- Add mathematical functions



Class 50, 110 & 210



As per following standards:

NF EN 12464-1 / NF EN 12464-2
NF EN 12193 (only for LX 200 luxmeters)



Hygrometers

HD 50 / 110
HQ 210

- 3 to 98 %RH
- -40 to +180 °C
- -50 to +80 °C_{td}
- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm

Luxmeters

LX 50 / 100 / 200

Illuminance measurement

- 0.1 to 200,000 lux
- 0.01 to 18,585 fc
- Operating software

Tachometers

CT 50 / 110

- Optical: 60 to 60,000 rpm
- Contact: 30 to 3,000 rpm



Refrigerant leak detector

DF 110

- Detection of all the HCFC and HFC refrigerants
- Detection of mixtures 5% hydrogen - 95% nitrogen (Nidron 5)
- Heated diode sensor
- Flexible hose



Manometers

MP 50 / 51 / 55 / 110 / 111
112 / 115 / 120 / 130 / 210

- Differential pressure
- ±500 Pa to ±2,000 mbar
- Air velocity with Pitot tube
- 3 to 85 m/s
- Atmospheric pressure
- 800 to 1,100 hPa



Anemometers

LV 50 / 110 / 111 / 117 / 130
VT 50 / 110 / 115 / 210

- Hotwire and telescopic hotwire
- 0.15 to 30 m/s
- Vane probes: Ø14, 70, 100 mm
- 0.3 to 35 m/s
- Airflow: 0 to 99,999 m³/h



The + of class 210 & 310

Designed for the field

An overmoulding made of elastomere protects the instrument, guarantees shockproofing.

Nonstop measurements

This new generation of instruments has an interchangeable and rechargeable Li-ion battery.

Expandable memory (AMI 310)

Internal memory of 1,000 datasets of 20,000 measuring points. Built-in location for a micro-SD memory card.

Interchangeable probes

The new probes utilise a mini-Din connecting cable which is compatible with all probes.

Interchangeable modules

1. Climatic conditions
2. Thermocouple (4 channels)
3. Pressure
4. U Coefficient



Accessories



ABS transport case



Protective housing



Backpack



Measuring cones



Debimo blades



Adjustable wedge for telescopic vane and hotwire probes



Pitot tubes

Multi-function

Class 310

AMI 310

AMI 310 is a multi-probe instrument which can measure up to 6 parameters simultaneously.



Wireless probes



Data processing software



Interchangeable probes & modules



Micro-SD card



Graphical display



Colour wide screen



- Pressure: ± 500 Pa / $\pm 2,500$ Pa / $\pm 10,000$ Pa / ± 500 mbar / $\pm 2,000$ mbar
- Thermocouple: -200 to $+1,760$ °C
- Pt100: -200 to $+600$ °C
- Humidity: 3 to 98 %RH

- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm
- Air velocity: -5 to 35 m/s
- Airflow: 0 to 99,999 m³/h
- Gas detection: 0 to 10,000 ppm
- Tachometry: 30 to 60,000 rpm

- Dew-point: -50 to $+100$ °C_{td}
- Wet temperature: -50 to $+100$ °C_{tw}
- Enthalpy: 0 to 10,000 kJ/kg
- Combination ratio: 0 to 10,000 g/kg
- Calculation of U coefficient and WBGT index



Thermometers

Portable instruments

Temperature

Class 210

TM 210

The differential thermometer TM 210 allows the temperature of 4 thermocouple probes to be taken simultaneously and the differential value to be displayed.

This instrument is suitable for any process where it is necessary to control the temperature at several points.

- Temperature: -200 to +1,760 °C
- 2 Pt100 channels
- 1,000 datasets storage
- Calculation of U coefficient
- 4 thermocouple inputs




Wireless probes



Elastomere overmoulding




Data processing software





Interchangeable measurement modules



Thermocouple module
4 inputs



U coefficient module



SMART+ probes

TT 21/22

- 1 or 2 inputs
- Thermocouple K, T
- K: -200 to +1300 °C
- T: -200 to +400 °C



TR 61/62

- 1 or 2 inputs
- Pt100
- -100 to +400 °C



TK 61/62

- 1 or 2 inputs
- Thermocouple K, J, T, S
- -200 to +1,760 °C



Hold/min/max functions



Large choice of probes



General use

- -20 to 40 °C
- Penetration probe



Infrared

KIRAY 100 / 200 / 300

- Diagnose, inspect and check any temperature, with the advantage of using "no-contact" technology
- -50 to +2,200 °C



MONITORING

Indoor air quality monitors

Service, Residential & Commercial Applications



Wireless pairing

IAQ analysis



Air quality

CO 50 / 110
AQ 110 / HQ 210

- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm
- -40 to +180 °C
- 3 to 98 %RH
- 0 to 5 m/s



Easy to use



Fonctions
Hold / Min / Max



Active Internal
Sampling Pump

By offering Indoor Air Quality (IAQ) professionals the ability to custom tailor their IAQ Monitors to meet their own specific requirements. Build your Indoor Air Quality monitor to detect for anywhere from one gas measurement (CO₂ only) up to seven total gas sensors in a single IAQ Monitor.

Si-AQ Comfort

CO₂, CO, Temperature, %RH, Wet bulb, Dew Point, Barometric pressure

Si-AQ VOC

Select up to 3 gases in total

COV, CO₂, CO, Formaldehyde, NO₂, NO, O₂, SO₂, H₂S

Si-AQ Expert

Select up to 7 gases in total

TVOC, CO₂, CO, Formaldehyde, NO₂, NO, O₂, O₃ (ozone), SO₂, H₂S

Si-AQ Pro

Select up to 3 gases:

CO₂, CO, NO₂, NO, SO₂, H₂S, Formaldehyde

Airflow meter

Airflow / Air velocity / Pressure




Airflow meter

DBM 620

Compatible with all air vent types.

- Interchangeable hoods
- Quick and easy mounting
- Simultaneous display of airflow and temperature
- Automatic airflow direction (extraction or air blast)
- From 35 to 4,250 m³/h (11 to 1,181 L/s)
- Supplied with 610x610 mm hood and transport case



Easily edit your reports with the SmartKap application



Switch between hoods quickly and easily



Patented folding frame & space-saving hoods storage



Transport case: compact storage system



Remote velocity grid

Designed for air velocity measurements on any type of large ceiling vent or diffuser.

- Average air velocity from 24 points
- Telescopic and articulated pole: maximum length 2.05 m, 0 to 90°, positioning strut
- Backpack

4 optional hoods are available:

- 2.36 x 2.36 ft (720 x 720 mm)
- 2.36 x 4.33 ft (720 x 1,320 mm)
- 1.38 x 4.99 ft (420 x 1,520 mm)
- 3.35 x 3.35 ft (1,020 x 1,020 mm)

PROCESS CONTROL

Data loggers

Kistock

Temperature / Humidity / Pressure / Air quality / Light
Current / Voltage / Pulse / Water pressure




**Up to
5 YEARS
battery life**



**Multi
Application**



**2 programmable
alarm thresholds**



**Up to 2,000,000
measuring points**



**Kilog software
(option)**




Anti-theft system

With the new range of Kistock stand-alone data loggers and Kilog software, you can collect and analyse all the metrics of industrial climate control engineering processes, monitor the

climatic environment of a chamber and respond to the traceability requirements of agri-food and pharmaceutical industries during transport.


ACCESSORIES



Probes



KNT 320




Kilog and Kilog-Lite



Anti-theft kit



Key benefits



Mobile application

- Wireless pairing
- Data visualisation
- Free download

Measuring element

Calibration data



Smart plug technology

Smart and interchangeable probes (class 320)

- Advanced technology
- Integrated calibration data



Mini

KH 50 / KT 50

Temperature, humidity

- -40 to +70 °C
- 5 to 95 %RH
- USB connection



Waterproof housing



USB

KH 120 / KT 120

Temperature, humidity

- -40 to +70 °C
- 5 to 95 %RH
- Integrated software
- USB connector



**KT 50 / KT 120
EN 12830**



Multi-function

KH 220 / KT 220 / KTT 220

Temperature, humidity, water pressure, light, current, voltage, pulse

- -200 to +1,760 °C
- 5 to 95 %RH
- 0 to 10,000 lux
- 0 to 20 bar
- 0 to 20 mA, 0 to 600 A
- 0 to 10 V



Interchangeable probes



Connected

KT 320 / KTT 320 / KCC 320
KPA 320 / KP 320-321

Temperature, humidity, pressure, atmospheric pressure, air quality, current, voltage, pulse

- -200 to +1,760 °C
- 5 to 95 %RH
- 0 to 5,000 ppm
- 800 to 1,100 hPa
- -10,000 to +10,000 Pa
- 0 to 20 mA, 0 to 600 A
- 0 to 10 V



Mobile application



Wireless pairing

Sensors

Transmitters

Pressure / Humidity / Temperature / Air velocity
Airflow / Air quality / Solar / Light



Industry, clean room, food industry

- For air processing
- Dip switch, keypad and software configuration
- Power supply: 24 V / 115 V / 230 V
- Outputs: 4-20 mA / 0-20 mA or 0-10 V / 0-5 V



Simplified calibration

Electronic board and measuring element connected to the front side of the sensor, which allows to configure and calibrate your device without causing any damage.



Monostats

PST / HST / TST / COST / CO2ST
1 RCR relay

- ± 100 Pa to $\pm 2,000$ mbar
- 5 to 95 %RH
- -100 to +400 °C
- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm



Class 110

CP / HM / TH / TM / CTV / CR / LR / CO
1 or 2 analogue outputs

- ± 100 Pa to $\pm 2,000$ mbar
- 800 to 1,100 hPa
- 5 to 95 %RH
- -100 to +400 °C
- 0 to 30 m/s

- 0 to 1,500 W/m²
- 0 to 10,000 lux
- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm



CO/CO₂ sensors

Sauermann designed CO/CO₂ transmitters in order to meet with requirements of new norms and decrees on air quality.

Multi-function

Class 210-R

CP / TH / TM / CTV / COT

2 analogue outputs
2 RCR relays
Calculation functions
Automatic autozero

- ± 100 Pa to $\pm 2,000$ mbar
- 0 to 100 %RH
- -100 to +400 °C
- CO: 0 to 500 ppm
- CO₂: 0 to 5,000 ppm
- 3 to 85 m/s (with Pitot tube) (CP 210)
- 0 to 30 m/s (with hotwire) (CTV 210)



SQR/3 option

Connected to DEBIMO measuring blades, CP 210-R can calculate air velocity and airflow in a duct, from differential pressure.

Multi-function

High-precision transmitters




2 INPUTS
for probes

Multi-function sensor


Si-C320

Graphical touch screen
Display and measure 4 parameters simultaneously
IP66 housing, VHP resistant
4 RCR relays (option)
4 analogue outputs
Wireless communication with mobile application (option)

- From -10 000 to +10 000 Pa
- From 0 to 100 %RH
- From -80 to +150 °C
- From 0 to 30 m/s
- From 0 to 99 999 m³/h
- CO: from 0 to 500 ppm
- CO₂: from 0 to 10 000 ppm
- COVT : from 0 to 1000 ppb
- CO₂eq : from 400 to 2000 ppm



**Multifunction for VAC
and IAQ applications**




4 analogue outputs



**4 visual and
audible alarms**



**RS-485 interface for
Modbus RTU protocol**



Other calculated parameters

- Absolute humidity, dew point, specific humidity, humidity temperature, enthalpy and freezing point.



Interchangeable probes

Si-C320 and Si-CPE320

Temperature / Humidity / Air velocity / CO / CO₂, ...



Flush-mount multi-function sensors Si-CPE320

- Special for clean room
- Front calibration
- 3 analogue outputs:
0-5/10 V or 0/4-20 mA
- From -250 Pa to +250 Pa



Calibration on the front side



3 visual and audible alarms



Brushed stainless steel 316L front face



Connection to a computer at the front

Large display sensor



Multi-function sensor CA 310

- 1 SPI-2 or MVA card input
- 3 RCR relays
- 3 analogue outputs: 0-5/10 V or 0/4-20 mA
- 3 visual and audible alarms

- From -10 000 to +10 000 Pa
- From 0 to 100 %HR
- From -50 to +180 °C
- From 3 to 85 m/s
- From 0 to 99 999 m³/h
- CO: from 0 to 500 ppm
- CO₂: from 0 to 5000 pp
- From 800 to 1100 hPa
- From 0 to 10 V
- From 0 to 20 mA



Interchangeable probes

CA 310
Temperature / Humidity / Air velocity / CO / CO₂, etc.


Data acquisition system

Pressure / Humidity / Temperature / Air velocity and Airflow

Data acquisition system

Configure / Display / Process / Export data

Easy setup, efficient monitoring of air movement condition, clean and cold rooms, test benches...



Calibration benches

Pressure / Humidity / Temperature

Pressure generator

GP 500

Calibration in laboratory or on-site
High accuracy
Automatic auto-zero



The pressure generator allows to adjust and calibrate measurement instruments in laboratory or on-site.

- -2,500 to +2,500 Pa
- -10,000 to +10,000 Pa



Temperature

Probes

Thermocouple / Pt100
Head / Cable / ABS Probes



CRYO and Wire probes




ABS head




Connection head



Measuring range
-200 to +1,150 °C



Calibration
-200 to +1,500 °C



Pt100
probes



Thermocouple
probes

Liquid column manometers

Differential pressure



Inclined

- 0-5 to 0-80 mmH₂O
- Units: Pa, daPa...



Vertical

- From 0-100 mmH₂O to 0-2.6 bar
- Units: mbar, Pa...



Differential pressure switch Si-DPMS

- Setting ranges in Pa:
20-200, 50-500, 200-1000, 500-2500,
1000-5000

ACCESSORIES


To fit any installation with
proper connections

- Liquid for manometer
- Tubes, junctions
- Pressure connections, wall-crossing
connection...



Our expertise

Manufacturing / Laboratories / R&D



Customer service portal

For all requests concerning repair, returns or calibration, connect to our Customer Service Portal.



Accessible
24h/7



Quick and
simple



Real-time
tracking

[Sauermann.site/Help](https://www.sauermann.com/site/Help)

State-of-the-art facilities and highly skilled staff

The Sauermann Group relies on cutting edge expertise, with more than 20 experts working in 1500 m² of testing and calibration laboratories around the world, with production lines in France, the United States and China. Our research

and development is conducted in-house by a young team of 20 engineers and 10 forward-thinking technicians. Their quest for innovation and patents is focused on ergonomics, digitalisation and connected devices, along with the constant improvement of the electronic and mechanical quality of our measuring instruments and condensate pumps.

Our in-house laboratories offer testing, adjustment and calibration services for a wide range of measuring instruments.

They are also one of the pillars of our high quality after-sales service. Our after-sales service covers multiple state-of-the-art activities to address all parameters related to indoor air quality.




Calibration
and adjustment



Repair /
maintenance




Hotline



Since more than 45 years, Sauermann has been developing its expertise in metrological services in many fields:

- Temperature
- Pressure
- Tachymetry
- Hygrometry
- Gas analysis
- Luxmetry
- Air flow rate
- Weighing
- Electricity
- Air velocity
- Radiometry



A new degree of efficiency

ADD A DIGITAL EDGE TO YOUR COMBUSTION ANALYSIS

Sauermann offers a range of compact and intuitive analysers to enhance your performance.



View and check from your smartphone



Generate and export measurement reports



Up to 6 calibrated gas sensors




Professional solutions for condensate management and indoor air quality measurement

INsights

Case studies, useful information and practical advice for HVACR and indoor air quality professionals.


sauermanngroup.com/insights



Sauermann on YouTube

Head to our YouTube channel for tutorials, webinars and product guides.

youtube.com/sauermanngroup



More information
sauermanngroup.com



Sauermann Industrie S.A.S
Route de Férolles
77173 Chevry-Cossigny - France

+33 (0)1 60 06 69 25
services@sauermanngroup.com